



Pankaj
Estd : 1959

ISO 9001:2015 Certified Company



ROTARY CONDUCTIVE PLASTIC POTENTIOMETER

MODEL RCP-22



WIRE WOUND SERVO POTENTIOMETERS
MODEL WWS-50

High Engineering Plastic Moulded Housing
50mm ϕ x 30mm Height,
Shaft 6mm ϕ x Length 15mm
100-10 K Ω
C Clamp for Mounting



SINGLE TURN WIRE WOUND POTENTIOMETERS
MODEL WP-1

High Engineering Plastic Moulded Housing & Cover
32mm ϕ x Length 17.50mm,
Shaft 6.3mm ϕ x Length 19mm or 25mm
Standard Resistance Value 100-10 K Ω



SQUARE POTENTIOMETERS
MODEL SQWW-55 WIRE WOUND
MODEL SQCP-55 CONDUCTIVE PLASTIC

High Engineering Plastic Moulded Housing
Gold Plated Contacts
55mm Square Potentiometers x 11mm Height
6mm Square Rotor
1K, 5K & 10K Ω

10 BIT HALL'S EFFECT CONTACTLESS SERVO ABSOLUTE ENCODERS

NCP-711



50mm ϕ x 50mm height
Shaft 8mm ϕ

NCP-711-V Voltage Output
NCP-711-S Voltage & Current Output
NCP-711-SSI SSI Output

Auxiliary Supply: 18-30VDC
Output 0-10VDC &/or 4-20mA &/or SSI

All outputs individually or in combination of two or three simultaneously can be used.

Pre-programmed angles of 45°, 60°, 90°, 180° and 360°

SINGLE TURN CONDUCTIVE PLASTIC SERVO POTENTIOMETER

RCP-35



35mm ϕ , 24.5mm Height,
Shaft 6mm ϕ , 15mm long,
360° Mechanical, 355° Electrical
Resistance: 1K, 5K or 10K Ω

RCP-50



50mm ϕ , 24.5mm Height,
Shaft 6mm ϕ , 15mm long,
360° Mechanical, 355° Electrical
Resistance: 1K, 5K or 10K Ω
C Clamp for Mounting

SINGLE TURN BUSH MOUNTING CONDUCTIVE PLASTIC POTENTIOMETER

SCP-25



25mm ϕ , 18mm Height
Resistance: 1K, 5K, 10K Ω

SHORT STROKE CONDUCTIVE PLASTIC POTENTIOMETER



20mm Sq., flange mounting
Resistance: 1K, 5K, 10K Ω

LINEAR MOTION WIRE WOUND POTENTIOMETERS LMP-WW-50..250



32mm Sq. Aluminium Anodized, S.S. Rod, Solenoid Connector Stroke Length: 50 to 250mm, Resistance Value: Upto 10K Ω
Sliding Mounting Clamp

WIRE WOUND SERVO POTENTIOMETERS

SS-50



Hollow Shaft
C Clamp for Mounting

Standard



15mm Shaft Length
50mm ϕ , x 30mm Height, Resistance: 100-10K Ω
C Clamp for Mounting

Rear Shaft Extension



Dual Ganged Rear
Shaft Extension with Hole

10 BIT MINI ABSOLUTE ENCODER

VE-360



Auxiliary Supply: 5VDC
Output 0-5VDC

SSIE-360



Auxiliary Supply: 5VDC
Output SSI

25mm ϕ x 18mm Height
Bush Mounting Absolute Encoder
Pre-programmed angles of 45°, 90°, 180° and 360°

POTENTIOMETERS WITH KNOB

PK-2320



SINGLE TURN WIRE WOUND POTENTIOMETERS



1 Watt, Res. 25 to 25K Ω
24mm ϕ x 16mm Height



3 Watt, Res. 25 to 25K Ω
40mm ϕ x 20mm Height



5 Watt, Res. 50 to 50K Ω
48mm ϕ x 28mm Height



7.5 Watt, Res. 50 to 50K Ω
48mm ϕ x 38mm Height



15 Watt, Res. 50 to 50K Ω
91mm ϕ x 38mm Height

FOOT OPERATED POTENTIOMETER WITH SWITCH
FOP-5K / 10K



Standard Switch Rating: 10Amp. @ 230VAC, 2NO + 2NC
Potentiometer: 1K, 5K or 10K Ω

PEDAL OPERATED POTENTIOMETER WITH SWITCH



POP-0417
Switch 10 Amp.
Pedal Potentiometer 5K Ω
Resettable Potentiometer 5K Ω

Dimensions, specifications and other details on our website: www.pankaj.com



Manufacturers & Exporters:

Pankaj POTENTIOMETERS PVT. LTD.

201-B, 217, 218 Udyog Mandir No.1, Pitamber Lane, Mahim, Mumbai 400016, India.
Phone: +91 22 24465778, 24458611 E-mail: pankaj.potentiometers@gmail.com

Estd : 1959



Note: We reserve the rights to make changes in Designs, Specifications and Functional Modifications at any time without prior notice.